

INDUCTIVE SENSORS

- IPS** = high precision ($H < 1 \mu m$)
- AC** = amplified a.c. 2 wire cylindrical body inductive series
- ACB** = amplified a.c. 3 wire cylindrical body inductive series
- ACF** = amplified a.c. 2 wire slot inductive series
- AX** = amplified a.c. + d.c. 2 wire 20 ÷ 240 V
- AXM** = amplified a.c. + d.c. 2 wire 10 ÷ 50 V
- DC** = cylindrical inductive NOT amplified d.c. NAMUR series 2 wires
- DCA** = cylindrical inductive amplified d.c. 3-4 wires
- DCAL** = cylindrical inductive analog linear output
- DCE** = extended sensing distance d.c. series
- DCF** = amplified d.c. slot series
- DF** = inductive slot sensors NOT amplified d.c. NAMUR series
- DSA** = amplified d.c. cylindrical SHORT body inductive series
- DSE** = extended sensing distance d.c. SHORT series
- DX** = amplified d.c. 2 wire 5 function series
- DCM** = amplified d.c. 2 wire non polarized

Diameter of cylindrical sensor or slot width for slot types.
For other types, change the number with the following:

- 80B** = diameter 80 mm
- P** = rectangular plastic 5 positions head 40 x 40 x 112
- R** = rectangular plastic with adjustable sensing distance 100 x 111 x 30
- T** = rectangular plastic 25 x 40 x 12
- X** = rectangular plastic 25 x 50 x 10
- Y** = rectangular plastic 30 x 50 x 15
- Z** = rectangular plastic 16 x 28 x 10

P = plastic housing

4 = flush mounting

5 = non flush mounting

DCA	18	P/	4	7	0	9	KS	-5	PUR
------------	-----------	-----------	----------	----------	----------	----------	-----------	-----------	------------

- 0** = with connector n° 17 - 18
- 1** = with connector n° 15 - 16
- 2** = 90° output with connector n° 1
- 3** = with connector M12 x 1
- 4** = with connector n° 1
- 6** = standard type cable output
- 7** = cable output with sheath holder
- 8** = with gland
- 9** = with connector M8 x 1
- A** = body length 50 mm completely threaded
- E** = with connector n° 2
- L** = side cable output
- *** = male connector wired on the sensor (see pag. H-1)

- 0** = NO (normally open output)
- 1** = NC (normally closed output)
- 2** = NO + NC (complementary outputs)
- C** = NC (output normally closed on pin 2 of connector)
- 5** = 5 functions sensor

- 0** = NAMUR series with 2 wires
- 8** = NPN
- 9** = PNP
- 9** = 20 ÷ 240 V. for a.c. sensors
- X** = 5 functions sensor

- L** = smooth body
- M** = stainless steel sensing face
- J** = degree of protection IP68
- K** = protection against short circuit and overload
- S** = LED output status
- T** = high temperature version
- V** = linear sensor with voltage output

Cable length (if required different than standard 2m)

For Polyurethane cable add PUR