

FX03872

Inductive Sensors BES IKU-031.28-S4 35 x 35 x 300 Complementary Sn=30mm unshielded

Common Data



Mounting in steel	unshielded
Rated operating distance Sn	30mm
Assured operating distance Sa	0...24.0mm
Repeatability R	≤ 5%
Hysteresis	≤ 15%
Function indication	yes
Ambient temperature range	-25...+70°C
Polution Degree	3

Mechanical Data

Measurements BxHxT or DxT	35 x 35 x 300mm
Housing material	Plastic
Material of sensing face	Plastic
Degree of protection	IP65IP
Connection	Connector S4 (M12)
Schock: Halfsinus, 30 gn, 11ms	
Vibration: 55 Hz, 1mm Amplitude, 3 x 30 Minutes	

Electrical Data

Current type	DC
Wiring	4-Wire
switching function	Complementary
Output signal	PNP
Rated operational voltage	24 DCV
Rated operational current	200mA
Supply voltage	10...30 DCV
Ripple	≤ 15%
max. switching frequency	50Hz
Minimum operational current	1.0mA
No-load supply current	≤ 10/≤ 10mA
Off-state current	-µA
Voltage drop	≤ 2.0/-V
Short circuit protection	no
Protected against polarity reversal	yes



Utilization categories
Insulation class

DC 13

Datasheet number:

Definitions see general catalog.
If not otherwise noted, ratings according to
IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH
Schurwaldstrasse 9
73765 Neuhausen a.d.F.
Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

BALLUFF
sensors worldwide