

**Inductive Sensors**  
**BES M08ME1-GSC20B-S04G**  
**M 8 x 1 x 50**  
**normally-open**  
**Sn=2mm**  
**shielded**

**Common Data**



Mounting in steel	shielded
Rated operating distance Sn	2mm
Assured operating distance Sa	0...1,6mm
Repeatability R	≤ 5%
Hysteresis	≤20%
Power indication	no
Function indication	yes
Ambient temperature range	-25...+70°C
Polution Degree	3
Time delay before availability	≤ 50ms

**Mechanical Data**

Measurements BxHxT or DxT	M 8 x 1 x 50mm
Housing material	CuZn, Nickel-free plated
Material of sensing face	PBTP
Degree of protection	IP67IP
Connection	Connector S4 (M12)
Schock: Halfsinus, 30 gn, 11ms	
Vibration: 55 Hz, 1mm Amplitude, 3 x 30 Minutes	

**Electrical Data**

Current type	DC
Wiring	2-Wire
switching function	normally-open
Rated operational voltage	24 DCV
Rated operational current	100mA
Supply voltage	10...30 DC polarizedV
Ripple	≤15%
max. switching frequency	1500Hz
Minimum operational current	5mA
Off-state current	≤ 600µA
Voltage drop	≤ 4V
Short circuit protection	yes
Protected against polarity reversal	yes



**Remarks**

When overload is removed, sensor resumed function



Utilization categories DC 13  
 Insulation class

Datasheet number:

Definitions see general catalog.  
 If not otherwise noted, ratings according to IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH  
 Schurwaldstrasse 9  
 73765 Neuhausen a.d.F.  
 Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

