

**Inductive Sensors**  
**BES Q40KEU-USU15B-S27G**  
**40 x 40 x 73**  
**normally-open**  
**Sn=15mm**  
**shielded**

**Common Data**


Product name	Unicomcompact
Mounting in steel	shielded
Rated operating distance Sn	15mm
Assured operating distance Sa	0...12mm
Repeatability R	≤ 5%
Hysteresis	≤ 20%
Function indication	yes
Ambient temperature range	-25...+70°C
Polution Degree	3
Time delay before availability	≤ 100ms

**Mechanical Data**

Measurements BxHxT or DxT	40 x 40 x 73mm
Housing material	PBT/Gd ZnAl4Cu1
Material of sensing face	PBT
Degree of protection	IP67IP
Connection	Connector S27
Schock: Halfsinus, 30 gn, 11ms	
Vibration: 55 Hz, 1mm Amplitude, 3 x 30 Minutes	

**Electrical Data**

Current type	AC/DC
Wiring	2-Wire
switching function	normally-open
Rated operational voltage	110 ACV
Rated operational current	250mA
Supply voltage	20...250 AC/DCV
Rated supply frequency	50/60/DCHz
max. switching frequency	100Hz
Minimum operational current	5mA
No-load supply current	-mA
Off-state current	≤ 1700µA
Maximum operational current	2/1mA
Voltage drop	≤ 11/≤ 7.5V
Short circuit protection	yes
Protected against polarity reversal	yes



Utilization categories AC  
 140/DC 13  
 Insulation class I

Datasheet number:

Definitions see general catalog.  
 If not otherwise noted, ratings according to  
 IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH  
 Schurwaldstrasse 9  
 73765 Neuhausen a.d.F.  
 Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

