



Technical Data

Size	186x48x30
Housing material	PA 6.6
Antenna	round
Weight	550 g
Function	Read/Write Head
Mounting in steel	non-flush
Operating temperature	0...70°C
Storage temperature	-20...85°C
Protection per IEC 60529	IP 65
Cable	PUR
Connection	Processor
possible cable length	5m or 10m
Description	read/write head, 186x48x30
Comments	At 10 m cable length, read/write distance is reduced by 10 %.

passender Datenträger

	BIS C-108-_/L-SA2 nicht bündig	BIS C-108-_/L nicht bündig	BIS C-117-05/L nicht bündig	BIS C-127-05/L nicht bündig	BIS C-128-_/L nicht bündig	BIS C-190-_/L nicht bündig
statischer Betrieb						
Schreibabstand in mm	0-7	8	8	38	8	8
Leseabstand in mm	0-7	8	8	38	8	8
Versatz in mm	1 mm	±8	±9	±9	±9	±9
bei Abstand von	5 mm	±5	±7	±7	±7	±7
	10 mm			±25		
	20 mm			±25		
	30 mm			±20		
	35 mm					
	42 mm					
	60 mm					
dynamischer Betrieb						
Schreib-/Leseweg in mm	60/70	70/80	70/80	70/80	70/80	60
Schreib-/Leseabstand in mm	5	6	6	20	6	5
V _{max} Schreiben von Byte 0...3 in m/min	36	42	42	42	42	36
V _{max} Lesen von Byte 0...3 in m/min	60	70	70	70	70	50