

Photoelectric Sensor BOS 21M-NA-LE10-S4 Sn=60000mm through-beam

Common Data



| | |
|-----------------------------------|-------------------------|
| Series | 21M |
| Sensortype | through-beam |
| Switching frequency | 1500 Hz |
| Rated operating distance Sn in mm | 60000 |
| asured operating distance Sa | 0...60000 |
| Repeat accuracy | < 1% |
| Hysteresis | < 20% |
| Indication Switching element on | yes |
| Indication Special funktion | Stability-indication |
| Ambient temperature | -10...+50°C |
| On-delay | = 0,33ms |
| Off-delay | < 1ms |
| Light | for red light |
| Sensitivity Adjustment | Poti |
| Special funktion | Stabilization indicator |
| Permissible ambient light | 5000 Lux |
| Output funktion | light-on |

Mechanical Data

| | |
|--------------------------|-----------------------------|
| Measurements | 50x42,5x15 |
| Shock | Halfsinus, 30gn, 11ms |
| Vibration | 55Hz, 1mm Amplitude 3x30Min |
| Housing material | Gd-Zn, Epoxy-coated |
| Material of sensing face | PMMA |
| Degree of protection | IP67 |
| Connection | Connector S4 (M12) |
| Weigth | 80g |

Electrical Data

| | |
|-------------------------------------|---------------|
| Current | DC |
| Switching funktion | NO/NC |
| Output | NPN |
| Rated operational voltage Ue | 24V DC |
| Rated operational current Ie | 100mA |
| Supply Voltage | 10...30V DC |
| Ripple | < 15% from UB |
| Frequency of Supply Voltage | DC |
| No-load supply current | <35mA |
| Voltage drop | <2V |
| Short protection | yes |
| Protected against polarity reversal | yes |
| Rated insulation voltage | 75VDC |
| max. Load capacity | =1000nF |



Utilization categories
Insulation class

DC 13
II

Datasheet number:

Definitions see general catalog.
If not otherwise noted, ratings according to
IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH
Schurwaldstrasse 9
73765 Neuhausen a.d.F.
Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

BALLUFF
sensors worldwide