

## Photoelectric Sensor BOS 21M-PA-PT10-S4 Sn=2000mm Retroreflective

### Common Data


Series	21M
Sensortype	Retroreflective
Switching frequency	1000 Hz
Rated operating distance Sn in mm	2000
asured operating distance Sa	0...2000
Repeat accuracy	< 2%
Hysteresis	< 20%
Indication Supply Voltage	no
Indication Switching element on	yes, yellow LED
Ambient temperature	-25...+55°C
On-delay	< 0,5ms
Off-delay	< 1ms
Light	Red light, 650nm, polarized
Wavelength / Laser protection class	detection of transparent objects
Sensitivity Adjustment	Poti
Special function	Stabilization indicator
Permissable ambient light	10000 Lux
Output function	light-on

### Mechanical Data

Measurements	50x42,5x15
Shock	Halfsinus, 30gn, 11ms
Vibration	55Hz, 1mm Amplitude 3x30Min
Housing material	Gd-Zn, Epoxy-coated
Material of sensing face	PMMA
Degree of protection	IP67
Connection	Connector S4 (M12)
Weigth	40g

### Electrical Data

Current	DC
Switching function	NO/NC
Output	PNP
Rated operational voltage Ue	24V DC
Rated operational current Ie	100mA
Supply Voltage	10...30V DC
Ripple	< 15% from UB
Frequency of Supply Voltage	DC
No-load supply current	<35mA
Voltage drop	<2V
Short protection	yes
Protected against polarity reversal	yes
Rated insulation voltage	75VDC
max. Load capacity	<1000nF



Utilization categories  
Insulation class

Datasheet number:

Definitions see general catalog.  
If not otherwise noted, ratings according to  
IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH  
Schurwaldstrasse 9  
73765 Neuhausen a.d.F.  
Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

**BALLUFF**  
sensors worldwide