

Photoelectric Sensor
BOS 25K-1-C90-02
Sn=900mm
Diffuse

Common Data


Series	25K
Sensortype	Diffuse
Switching frequency	2000 Hz
Rated operating distance Sn in mm	900
asured operating distance Sa	adjustable
Repeat accuracy	< 5% from Sn
Hysteresis	< 10%
Indication Switching element on	yes, red LED
Ambient temperature	-15...+55°C
On-delay	< 30ms
Off-delay	< 30ms
Light	Infrared
Sensitivity Adjustment	Poti
Blind zone / min Reflector distance	1mm / -
Permissable ambient light	3000 Lux
Output function	light-on or dark-on

Mechanical Data

Measurements	50x50x16
Shock	Halfsinus, 30gn, 11ms
Vibration	10...55Hz, 1,5mm Amplitude 3x2h
Housing material	ABS UL 94 V-O
Material of sensing face	PMMA
Degree of protection	IP65
Connection	Cable
Weigth	160g
Type of Cable	PVC

Electrical Data

Current	AC/DC
Switching function	NO/NC
Output	Relais
Rated operational voltage Ue	24V DC
Supply Voltage	15...264V AC/DC
Ripple	max. 6% from UB
Frequency of Supply Voltage	AC/DC
Short protection	yes
Rated insulation voltage	250V AC



Utilization categories
 Insulation class

Datasheet number:

Definitions see general catalog.
 If not otherwise noted, ratings according to
 IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH
 Schurwaldstrasse 9
 73765 Neuhausen a.d.F.
 Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

BALLUFF
 sensors worldwide