

Photoelectric Sensor
BOS 5K-NO-RD11-S75
Sn=200mm
Diffuse

Common Data


Series	5K
Sensortype	Diffuse
Switching frequency	500 Hz
Rated operating distance Sn in mm	200
asured operating distance Sa	adjustable
Indication Supply Voltage	yes, green LED
Indication Switching element on	yes, yellow LED
Ambient temperature	-25...+55°C
On-delay	1ms
Off-delay	<0,5ms
Light	Red light, 660nm
Sensitivity Adjustment	Poti 270°
Permissable ambient light	5000 Lux
Output function	dark-on

Mechanical Data

Measurements	42,3 x 19,5 x 10,8
Housing material	PC/PBT
Material of sensing face	PC
Degree of protection	IP67
Connection	Connector S75 (M8,4-pin)
Weigth	10g

Electrical Data

Current	DC
Switching function	normally-closed
Output	NPN
Rated operational voltage Ue	24V DC
Rated operational current Ie	100mA
Supply Voltage	10...30V DC
Frequency of Supply Voltage	DC
No-load supply current	<30mA
Voltage drop	<1,2V
Short protection	yes
Protected against polarity reversal	yes



Utilization categories
 Insulation class

Datasheet number:

Definitions see general catalog.
 If not otherwise noted, ratings according to
 IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH
 Schurwaldstrasse 9
 73765 Neuhausen a.d.F.
 Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

