

PX1946

Photoelectric Sensor BOS 5K-PO-RR10-S75 Sn=4000mm Retroreflective

Common Data


| | |
|-----------------------------------|------------------|
| Series | 5K |
| Sensortype | Retroreflective |
| Switching frequency | 500 Hz |
| Rated operating distance Sn in mm | 4000 |
| asured operating distance Sa | adjustable |
| Indication Supply Voltage | yes, green LED |
| Indication Switching element on | yes, yellow LED |
| Ambient temperature | -25...+55°C |
| On-delay | 1ms |
| Off-delay | <0,5ms |
| Light | Red light, 660nm |
| Sensitivity Adjustment | Poti 270° |
| Permissable ambient light | 5000 Lux |
| Output function | light-on |

Mechanical Data

| | |
|--------------------------|--------------------------|
| Measurements | 42,3 x 19,5 x 10,8 |
| Housing material | PC/PBT |
| Material of sensing face | PMMA |
| Degree of protection | IP67 |
| Connection | Connector S75 (M8,4-pin) |
| Weigth | 10g |

Electrical Data

| | |
|-------------------------------------|-----------------|
| Current | DC |
| Switching function | normally-closed |
| Output | PNP |
| Rated operational voltage Ue | 24V DC |
| Rated operational current Ie | 100mA |
| Supply Voltage | 10...30V DC |
| Frequency of Supply Voltage | DC |
| No-load supply current | <30mA |
| Voltage drop | <1,2V |
| Short protection | yes |
| Protected against polarity reversal | yes |



Utilization categories
Insulation class

Datasheet number:

Definitions see general catalog.
If not otherwise noted, ratings according to
IEC 60947-5-2 (DIN EN60947-5-2)

Balluff GmbH
Schurwaldstrasse 9
73765 Neuhausen a.d.F.
Phone (07158) 173-0 Fax (07158) 5010

Datenblatt by CD-ROM - 04/2007

BALLUFF
sensors worldwide