

Sandwich pressure regulator with manual adjust.

OPERATIONAL BENEFITS

1. Easy mounting : saves on installation costs in comparison with inline regulators.
2. Allows to have compact, all-included units.
3. Large orifice provides high flow.
4. Various functions available.
5. Simple, reliable and solid design.



HOW TO ORDER

Reset

REGULATORS FOR "PLUG-IN" VALVES

Gauges	Single pressure Regulator B end Same regulated pressure to ports A and B
No gauge	PR62C-21AA
Non filled gauge	PR62C-21FA
Glycerine filled gauge	PR62C-21BA

REGULATORS FOR "NON PLUG-IN" AND REMOTE AIR VALVES

Gauges	Single pressure Regulator B end Same regulated pressure to ports A and B
No gauge	PR62C-31AA
Non filled gauge	PR62C-31FA
Glycerine filled gauge	PR62C-31BA

**TECHNICAL
DATA**

Fluid :	Compressed air, inert gases
Pressure range :	0 to 10 bar
Regulating range :	0.5 to 8.5 bar
Lubrication :	Not required, if used select a medium aniline point lubricant (between 80°C and 100°C)
Filtration :	40 µ
Temperature range :	-18°C to +50°C
Flow (at 6 bar, ΔP=1bar) :	1250 NI/min (C _v 1.25)

Spare parts : • Pressure regulator : PR62C-01AA.

DIMENSIONS

