

Plug-in sandwich pressure regulator with air pilot adjust

OPERATIONAL BENEFITS

- 1. Easy mounting: saves on installation costs and space in comparison with inline regulators
- 2. Compact all-included units.
- 3. Large orifice provides high flow.
- 4. Various functions available.
- 5. Simple, reliable and solid design.

HOW TO ORDER

Pilot	Single pressure Regulator 12 end	Dual pressure * Regulator 12 end with by-pass 14 end	Dual pressure * Regulator 14 end with by-pass 12 end	Dual pressure * Regulator both ends
Internal	PRP01A-DAAA	PRP01A-DBAA	PRP01A-DDAA	PRP01A-DEAA
External	PRP01A-EAAA	PRP01A-EBAA	PRP01A-EDAA	PRP01A-EEAA

Note: Only pressure range available for air adjust is 0-8 bar.

* To be used with dual pressure valves



TECHNICAL DATA

Fluid:	Compressed air, inert gases
Pressure supply:	Higher than maximum regulated pressure (max 8,5 bar)
Regulating range:	0 to 8 bar
Lubrication:	Not required, if used select a medium aniline point lubricant (between 80°C and 100°C)
Filtration:	40µ
Temperature:	-18°C to +50°C

DIMENSIONS

