


SERVO CABLES

GAALFLEX® SERVO T 834 C

TPE/PUR with overall copper screen, acc. to SIEMENS standard 6FX8008



ELETTROTEK KABEL® GAALFLEX® SERVO T 834 C



Construction:

Conductor:	flexible red copper conductor Cl. 6 acc to IEC 60228, DIN VDE 0295
Insulation:	special TPE compound
Colour cores:	black cores with consecutive numbers acc. to EN 50334 green-yellow from 3 cores 0,34 mm ² : acc. to DIN 47100
Stranding:	in layers + fillers
Wrapping:	non-woven tape
Screen:	tinned copper braid
Outer sheath:	orange (RAL 2003), PUR compound, acc. to UL 758

Resistance:

	Self-extinguishing and flame retardant acc. to: IEC 60332-1-2 EN 60332-1-2 UL CSA FT-1, FT-2
	Oil resistance acc. to: DIN VDE 0473 part 811-2-1, IEC 60811-2-1
	Halogen free acc. to: IEC 60754-1 (equivalent DIN VDE 0472 part 815)

Technical data:

Nominal voltage:	U ₀ /U 0,6/1 kV	UL/CSA: 1000 V
Test voltage:	4 kV x 5 min 4 kV x 1 min	
Temperature range	DIN VDE	UL/CSA: up to +80°C
<i>Fixed laying:</i>	- 50°C up to + 90°C	
<i>Flexible installation:</i>	- 40°C up to + 90°C	
Radiation resistance:	5 x 10 ⁷ cJ/kg	
Min. bending radius		
<i>Fixed laying:</i>	5 x d	
<i>Flexible installation:</i>	7 x d	
<i>Continuously flexible:</i>	7 x d	
Max speed (main application):	300 m/min	

Features:

UL AWM style 21223 80°C, 1000V
CSA AWM I/II A/B 80°C 1000 V FT1 FT2
low capacitance
very high flexibility
oil resistant
very long service life
adhesion-free installation
labs uncritical
flexible at low temperature
DESINA® colours
for SPEEDS and MINIMUM BENDING RADIUS
see pages from 2 to 8 of catalogue
RoHS and CE approval



SIEMENS

Part no.	acc.to SIEMENS Standard	No. of cores x cross section n x mm ²	Outer-Ø ca. mm ± 10%	Copper weight kg/km	Cable weight approx. kg/km	AWG no. *)
37080HG0041A16	6FX8008-1BB11	4 G 1,5	9,1	83,5	126	16
37080HG0041A14	6FX8008-1BB21	4 G 2,5	11	142,5	192	14
37080HG0041A12	6FX8008-1BB31	4 G 4	12,5	206,7	273	12
37080HG0041A10	6FX8008-1BB41	4 G 6	15,5	298,3	399	10
37080HG0041A08	6FX8008-1BB51	4 G 10	17,8	495,2	605	8
37080HG0041A06	6FX8008-1BB61	4 G 16	22,8	750	951	6
37080HG0041A04	6FX8008-1BB25	4 G 25	25,7	1120	1331	4
37080HG0041A02	6FX8008-1BB35	4 G 35	29,2	1534	1732	2
37080HG0041A01	6FX8008-1BB50	4 G 50	34,3	2144	2428	1
37080HG0041A2C	6FX8008-1BB70	4 G 70	39,9	3029	3803	2/0

Other dimension and colours available on request.